

RRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRR			•
	\$		

-

16 :* 17 :*

18 : *

20 *

16-SEP-1984 00:44:41 VAX/VMS Macro V04-00 5-SEP-1984 01:08:57 [F11A.SRC]REQUEU.MAR;1

Page 1 (1)

.TITLE REQUEU - REQUEUE REQUEST TO DRIVER .1DENT 'V04-000'

COPYRIGHT (c) 1978, 1980, 1982, 1984 BY DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS. ALL RIGHTS RESERVED.

THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY TRANSFERRED.

THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT CORPORATION.

DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.

FACILITY: F11ACP STRUCTURE LEVEL 1

ABSTRACT:

THIS ROUTINE REQUEUES THE INDICATED I/O PACKET TO THE DEVICE DRIVER FOR WHICH IT WAS ORIGINALLY INTENDED.

ENVIRONMENT:

STARLET OPERATING SYSTEM, INCLUDING PRIVILEGED SYSTEM SERVICES AND INTERNAL EXEC ROUTINES. THIS ROUTINE MUST BE CALLED IN KERNEL MODE.

AUTHOR: ANDREW C. GOLDSTEIN 14-MAR-78 10:43

MODIFIED BY:

V03-001 RLRMXBCNT Robert L. Rappaport 11-Mar-1983 Allow for segmentation of Logical I/O (and Virtual) based on the UCB\$L_MAXBCNT field.

EQUATED SYMBOLS:

D 11 16-SEP-1984 00:44:41 VAX/VMS Macro V04-00 5-SEP-1984 01:08:57 [F11A.SRC]REQUEU.MAR;1 - REQUEUE REQUEST TO DRIVER Page 2 (1) 00000004 0000 00000008 0000 00000000 0000 58 PACKET = 4 59 BN = 8 60 UNMAPPED= 12 ; ADDRESS OF I/O PACKET ARG ; STARTING LBN OF TRANSFER ; COUNT OF UNMAPPED BLOCKS 0000 61 62 : DEFINE I/O PACKET OFFSETS : DEFINE I/O FUNCTION CODES : DEFINE UCB OFFSETS SIRPDEF SIODEF 0000 64 SUCBDEF

REQUEU VO4-000 0000

REQUEU

V04-000

```
(2)
```

V

```
66 :++
                            0000
                            0000
                                          FUNCTIONAL DESCRIPTION:
                            0000
                                     70
                            0000
                                                 THIS ROUTINE REQUEUES THE INDICATED I/O PACKET TO THE DEVICE
                                     71
                            0000
                                                 DRIVER FOR WHICH IT WAS ORIGINALLY INTENDED. IT TRANSLATES THE
                                     72
73
                            0000
                                                 LBN INTO THE CORRESPONDING PHYSICAL BLOCK NUMBER AND CONVERTS THE
                            0000
                                                 I/O FUNCTION CODE INTO THE APPROPRIATE PHYSICAL FUNCTION.
                            0000
                                                 THE NUMBER OF UNMAPPED BLOCKS IS DEDUCTED FROM THE BYTE COUNT.
                                     75
                            0000
                                     76
77
                            0000
                                          CALLING SEQUENCE:
                            0000
                                                 CALL REQUEUE_REQ (ARG1, ARG2, ARG3)
                                     78
                            0000
                                     79
                                           INPUT PARAMETERS:
                            0000
                                     80
                            0000
                                                 ARG1: ADDRESS OF I/O PACKET
                                     81
                            0000
                                                 ARG2: STARTING LBN OF TRANSFER
                            0000
                                                 ARG3: NUMBER OF BLOCKS UNMAPPED
                                     83
                            0000
                            0000
                                          IMPLICIT INPUTS:
                                     85
                            0000
                                                 CURRENT_UCB: ADDRESS OF REQUEST UCB
                            0000
                                     87
                                           OUTPUT PARAMETERS:
                            0000
                                     88
                            0000
                                                 NONE
                                     89
                            0000
                                     90
                            0000
                                          IMPLICIT OUTPUTS:
                                     91
                            0000
                                                 NONE
                            0000
                            0000
                                           ROUTINE VALUE:
                                     94
                            0000
                                                 NONE
                                     95
                            0000
                            0000
                                          SIDE EFFECTS:
                                     97
                            0000
                                                 REQUEST QUEUED TO UCB
                            0000
                                     98
                            0000
                                     99
                            0000
                                    100
                        0000000
                                    101
                                                 .PSECT $CODE$, NOWRT, LONG
                            0000
                            0000
                                    103
                                        REQUEUE_REQ::
                     003C
                            0000
                                    104
                                                          ^M<R2,R3,R4,R5>
                                                 .WORD
                                                                                       SAVE REGISTERS
               04 AC
                                    105
                                                                                       GET PACKET ADDRESS
         53
                            0002
                                                          PACKĒŤ(AP),Ř3
                        DO
                                                 MOVL
       55
            0000 CF
                                    106
                            0006
                                                                                      GET UCB ADDRESS
                        D0
                                                 MOVL
                                                          W^CURRENT_UCB,R5
                                                          #9 UNMAPPED (AP) ,RO
                        78
         OC AC
                  09
                            000B
                                                 ASHL
                                                                                       GET BYTE COUNT OF UNMAPPED BLOCKS
                        13
                                                                                       BRANCH IF ALL MAPPED - NO FIXUP
                            0010
                                    108
                                                 BEQL
                                                          RO, IRP$L BCNT(R3)
#511, IRP$L BCNT(R3)
#511, IRP$L BCNT(R3)
                       (5)
                                    109
                                                                                       AND SUBTRACT FROM TRANSFER COUNT
                  50
                            0012
                                                 SUBL
        000001FF
                  8F
                            0016
                                    110
                                                                                       ROUND BYTE COUNT TO NEXT BLOCK BOUNDARY
32 A3
                                                 ADDL
    32
             01FF
                  8F
                                                                                       IN CASE FULL BYTE COUNT CONTAINS A PARTIAL
       A3
                        AA
                            001E
                                    111
                                                 BICW
                        DO
12
30
                                                          UCB$L_MAXBENT(R5),RO
                                    112
       50
             00B4
                  C5
                            0024
                                        105:
                                                 MOVL
                                                                                       RO = 0 or Max. permissible BCNT.
                            0029
                                                          20$
                                                 BNEQ
                                                                                       NEQ implies Max. permissible BCNT in RO.
       50
             FE00
                            002B
                                    114
                                                 MOVZWL
                                                          #512+127,RO
                                                                                      If 0, use default Max. permissible.
                  8F
                            0030
                                    115 20$:
                                    116
                            0030
                                                          RO, IRP$L_BCNT(R3) 30$
          32 A3
                  50
                        D1
                                                 CMPL
                                                                                       See if BCNT too large.
                  04
                        18
                            0034
                                                 BGEQ
                                                                                       GEQ implies we are OK.
          32 A3
                  50
                        D0
                            0036
                                                          RO, IRP$L_BCNT(R3)
                                    118
                                                 MOVL
                                                                                     ; Else scale down to maximum allowed.
                                    119 305:
                            003A
                                    120
121
122
        50 08 AC 0000000 9F
                                                                                       GET STARTING LBN
                        D0
                            003A
                                                 MOVL
                                                          LBN(AP),RO
                        16
                            003E
                                                 JSB
                                                          a#IOC$CVTLOGPHY
                                                                                       CONVERT TO PHYSICAL BLOCK
                                                          aMEXESINSIOQ
        00000000°9F
                            0044
                                                 JSB
                                                                                     : AND QUEUE TO DRIVER
```

F 11 (2) REQUEU VO4-000 - REQUEUE REQUEST TO DRIVER 16-SEP-1984 00:44:41 VAX/VMS Macro V04-00 5-SEP-1984 01:08:57 [F11A.SRC]REQUEU.MAR;1 04 004A 004B 004B 004B 004B RET .END

```
REQUEU
                                                                                          16-SEP-1984 00:44:41 VAX/VMS Macro V04-00 5-SEP-1984 01:08:57 [F11A.SRC]REQUEU.MAR;1
                                        - REQUEUE REQUEST TO DRIVER
                                                                                                                                                        Page
                                                                                                                                                               (2)
Symbol table
AGB TYP
BITMAP YPE
CURRENT_UCB
                                      = 00000005
                                      = 00000001
                                                           02
                                         ******
                                                      X
DIRECTORY TYPE
                                       = 00000002
EXESINSIO
                                                           02
                                         ******
FCB TYPE
HEADER TYPE
INDEX TYPE
IOCSCVILOGPHY
                                      = 00000000
                                      = 00000000
                                      = 00000003
                                                           02
                                         ******
IRP$L_BCNT
                                      = 00000032
LBN
MVL TYPE
PACKET
                                      = 00000008
                                      = 00000004
                                      = 00000004
REQUEUE REQ
                                         00000000 RG
                                                           02
RVT_TYPE
UCB$L_MAXBCNT
                                      = 00000003
                                      = 00000084
UNMAPPED
                                      = 0000000c
VCB_TYPE
WCB_TYPE
                                      = 00000002
                                      = 00000001
                                                             Psect synopsis!
PSECT name
                                        Allocation
                                                                PSECT No.
                                                                              Attributes
  ABS
                                        00000000
                                                                       0.)
                                                                              NOPIC
                                                          0.)
                                                                00 (
                                                                                       USR
                                                                                               CON
                                                                                                      ABS
                                                                                                              LCL NOSHR NOEXE NORD
                                                                                                                                         NOWRT NOVEC BYTE
SABSS
                                        00000000
                                                          0.)
                                                                              NOPIC
                                                                01
                                                                    (
                                                                       1.)
                                                                                       USR
                                                                                               CON
                                                                                                      ABS
                                                                                                              LCL NOSHR
                                                                                                                            EXE
                                                                                                                                    RD
                                                                                                                                           WRT NOVEC BYTE
$CODE$
                                                         75.)
                                       0000004B
                                                                02 (
                                                                       2.)
                                                                              NOPIC
                                                                                       USR
                                                                                               CON
                                                                                                      REL
                                                                                                                            EXE
                                                                                                                                    RD
                                                                                                                                         NOWRT NOVEC LONG
                                                                                                              LCL NOSHR
                                                        ! Performance indicators !
Phase
                               Page faults
                                                 CPU Time
                                                                    Elapsed Time
                                                 00:00:00.13
00:00:00.75
00:00:07.61
00:00:01.39
00:00:01.37
                                       30
130
270
Initialization
                                                                    00:00:00.96
                                                                    00:00:04.64
Command processing
Pass 1
                                                                    00:00:20.96
                                                                    00:00:02.50
00:00:04.88
Symbol table sort
Pass 2
                                         41
Symbol table output
                                                 00:00:00.05
                                                                    00:00:00.05
Psect synopsis output
                                                 00:00:00.02
                                                                    00:00:00.02
                                                 00:00:00.00
00:00:11.33
```

00:00:00.00

00:00:34.02

The working set limit was 1350 pages.
41203 bytes (81 pages) of virtual memory were used to buffer the intermediate code.
There were 50 pages of symbol table space allocated to hold 870 non-local and 3 local symbols.
230 source lines were read in Pass 1, producing 13 object records in Pass 2.
14 pages of virtual memory were used to define 13 macros.

479

Cross-reference output

Assembler run totals

REQUEU VAX-11 Macro Run Statistics

- REQUEUE REQUEST TO DRIVER

16-SEP-1984 00:44:41 VAX/VMS Macro V04-00 5-SEP-1984 01:08:57 [F11A.SRC]REQUEU.MAR;1

Page 6 (2)

Macro library statistics !

Macro Library name Macros defined
\$255\$DUA28:[SYS OR I] IR MIR:1

_\$255\$DUA28:[SYS.OBJ]LIB.MLB;1 _\$255\$DUA28:[SYSLIB]STARLET.MLB;2 TOTALS (all libraries)

4

920 GETS were required to define 6 macros.

There were no errors, warnings or information messages.

MACRO/LIS=LIS\$:REQUEU/OBJ=OBJ\$:REQUEU MSRC\$:FCPPRE/UPDATE=(ENH\$:FCPPRE)+MSRC\$:REQUEU/UPDATE=(ENH\$:REQUEU)+EXECML\$/LIB

0166 AH-BT13A-SE

DIGITAL EQUIPMENT CORPORATION CONFIDENTIAL AND PROPRIETARY

